

Video 20 Plus. Video 20 Sensor. The smartest heads... ... for changing viewpoints.

In contrast to the Video 18 Plus line. Video 20 Plus heads offer you a significantly higher carrying capacity, a continuous seven-step counterbalance system, and a longer balance plate sliding range. Dust shields prevent dirt particles from penetrating the heads.



Video 20 Plus. More carrying power.

Even more carrying power combined with increased carrying capacity allow the Video 20 Plus to be used even for EFP applications. Rear camera operation? On-camera viewfinder monitors? No problem for the powerful Video 20 Plus.

Video 20 Sensor.
Electronics for the highest degree of precision positioning.

In addition to all the features of the Plus line, the Sensor model offers an LED display that allows you to precisely position the camera's balance plate, thus optimally compensating for the camera weight. You can determine counterbalance just as precisely. Do you want to add a light or use a heavy lens? The Sensor's electronics measure dynamic counterbalance and display the optimal setting for you. So even when you have to swap cameras, you'll be ready to roll again in the blink of an eye. Your camerawork is perfect.

Technical data:
Video 20 Sensor
Code No.: 2000S
Weight: 3.6 kg (7.9 lb.)
Bubble level battery: 4X625PX.
Additional data such as Video20 Plus

Technical data:
Video 20 Plus
Code No.: 2000P
FB Converter
Code No.: 3913
(for flat base connection)
Counterbalance system :
12 to 48 Nm /approx.7 to 27 kg/15 to 59 lb. (110mm center of gravity height)
Balance plate: 110 mm (4.4 ins) sliding range
Grades of drag: 7 each horizontal and vertical, 0
Tilt angle: ±90° with any camera weight
Temperature range:
-40° C to +60° C (-40° F to +140° F)
Weight: 3.5 kg (7.7 lb.)
Maximum load: 25kg (55lb.)
Camera fitting: Touch & Go camera plate 16 with 1/4 ins and 3/8 ins screw
Tripod fitting:
100mm half-ball and flat base adapter for all pedestals
Pan bars: Two, with mounting diameter of 18/22 mm/0.71/0.87 ins, 350 to 520mm /13.8 to 20.5 ins length.
Bubble level illumination:
Adjustable between 20 and 45 sec.
Bubble level battery: 3X625PX.

System 20 Sensor on ENG2 MCF

SYSTEMS VIDEO 20



System 20 Plus ENG 2 CF
Code No.: 2032P

Video 20 Plus + ENG 2CF tripod + SP 100 spreader + ENG 2 bag

System 20 Plus ENG 2 MCF
Code No.: 2032PG

Video 20 Plus + ENG 2 CF tripod + off-ground spreader + rubber feet + ENG 2 bag

Super Plus Kit
System 20 Plus ENG 2 HD CF
Code No.: 2033P
Super20Plus HD MCF
Code No.: 2034PG

Video 20 Plus + ENG 2 CF HD tripod + SP 100/150 spreader

Video 20 Plus + ENG 2 CF HD tripod + off-ground spreader + rubber feet + ENG/EFP bag

Super20 Sensor ENG2 MCF
Code No.: 2032S

Video 20 Sensor + ENG 2 CF tripod + off-ground spreader + rubber feet + ENG 2 bag